



MRD-120

Order No.: 10.4110

Price upon request

PRODUCTINFOS

PA horn driver, 50 W, 8 Ω

- 35 mm (1 $\frac{3}{8}$ ") standard thread
- Good, extensive frequency response linearity
- High sound pressure level with low distortions
- Excellent allround driver for almost any PA application, also in combination with 38 cm (15") bass-midrange speakers or in any multi-way system, of course
- Replacement voice coil MRD-120/VC is available at option
- Suitable for horns MRH-83, MRH-170 and MRH-80

TECHNICAL SPECIFICATIONS

MRD-120

Impedance (Z)	8 Ω
Frequency range	fx-17,500 Hz
Resonant frequency (fs)	1,300 Hz

MRD-120

Rec. crossov. frequ. (fmax.) (12 dB/oct.)	3,000 Hz
Power rating	50 W
Peak music power output	100 W
Sensitivity	107 dB/W/m
Voice coil diameter	Ø 38 mm
Magnet diameter	120 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Dimensions	Ø 120 mm x 85 mm
Outside diameter	Ø 120 mm
Width	Ø 120 mm
Depth	85 mm
Admiss. ambient temp.	0-40 °C
Weight	1.8 kg